



# PRODUCT DATA SHEET

## Havens GEO SAE 40

### DESCRIPTION

Premium CNG/LNG oil formulated to deliver outstanding protection and long drain performance in a wide variety of compressed natural gas (CNG), liquefied natural gas (LNG) and liquefied petroleum gas (LPG) stationary engine applications.

### PROPERTIES

This lubricant assures:

- Alternative fuel performance:
- Great performance for medium and heavy-duty engines using CNG, LNG or LPG.
- Excellent engine cleanliness
- Sludge control; and valve, or piston deposits in field trials and engine tests.
- Oil oxidation/nitration control

### APPLICATIONS

Wide variety of compressed natural gas (CNG), liquefied natural gas (LNG) and liquefied petroleum gas (LPG) engines

### TYPICAL PROPERTIES

Havens GEO SAE 40		
Typical Properties	SAE Grade	40
	API level	CF
Test Parameters	ASTM Method	Typical Values
Density @ 15°C, kg/l	ASTM D1298	0.880
Viscosity @ 100°C, cSt	ASTM D445	13.5
Flash Point, °C	ASTM D92	255
BN, mg KOH/g	ASTM D2896	5.5
Pour Point, °C	ASTM D97	-25

October 2018

*The values shown above are typical values at the date of publication. Havens Lubricants reserves the right to change these typical values without prior notice.*